



## PRODUCT DATA SHEET for 2000-461

**Facestock:**

Thickness: 2 mil Thermoplastic Film Thermal-Transfer Printable

**Adhesive:**

Cold temperature adhesive. High initial tack. 0.3 mil Thickness

**Support Liner:**

Thickness: 1.5 mil Clear Poly Liner

**Lower resistance temperature:**

-196°C (-321°F)

**Upper resistance temperature limit:**

+100°C (+212°F)

**Minimum Application Temperature:**

-12°C (10°F)

**Storage Stability:**

At least 1 year at 72°F (22°C) and 50% RH

**Label Dimensions:**

Height: 0.25"(6mm); Length: 0.80"(20mm); Printable Length: 0.80"(20mm); Span: 0.9375"(24mm)

**FDA Compliance:**

Compliant with FDA 21 CFR 175.105. Compliance to this regulation permits the use of this adhesive in applications for which the adhesive either (1) is separated from the food by a functional barrier, which will prevent the migration of any of the adhesive components to the food, or (2) has incidental contact with food limited to the trace amount at the seams or the edges of the label.

**RoHS Compliance:**

Compliant with the substance restrictions in EU Directive 2002/95/EC, as amended (Restriction of the use of certain Hazardous Substances in Electrical and Electronic Equipment), and / or in the recast RoHS Directive 2011/65/EU. Does not contain decabromodiphenyl ether (Deca-BDE).

The specifications provided herein are based on the information supplied by primary material manufacturer (s) and tests conducted by the label manufacturer. The end-user shall independently determine the suitability of the labels for the purpose for which they were purchased.